

**Series 2, canopy cooker hood, 53 cm,
Stainless steel
DLN53AA50B**



DWZ0IN0A0 Standard odor filter (replacement)
DWZ0IN0T0 Standard recirculation kit

The canopy cooker hood: offers you flexibility in your kitchen planning - mount it either on the wall or above a kitchen island.

- **Silent:** maximal extractor performance with little noise
- **Metal Grease Filter:** cleans the air, captures grease, easy monthly clean-up.
- **3-Speed Power Level Options To Suit Your Cooking Style And Recipes**

Typology: Built-in/Built-under
Length electrical supply cord: 150 cm
Required niche size for installation (HxWxD): ... 208mm x 493.0mm x 257mm mm
Net weight: 4.3 kg
Type of control: mechanical
Number of speed settings: 3
Max. air extraction: 300 m³/h
Max. air recirculation: 300 m³/h
Number of lights: 2
Noise level: 61 dB(A) re 1pW
Diameter of air outlet: 120 mm
Grease filter material: Washable aluminium
Odour filter: No
Operating Mode: Convertible
Optional accessories: DWZ0IN0A0, DWZ0IN0T0
Type of lamps used: Not applicable
Total power of the lamps: 6 W
Grease filter type: Kassette
Clean filter reminders: No
Connection rating: 121 W
Fuse protection: 5 A
Voltage: 220-240 V
Frequency: 50 Hz
Plug type: GB plug
Installation typology: Built-in
Material body: Stainless steel
Plug type: GB plug
Dimensions of the product, with chimney (if exists) (in): x x
Dimensions of the packed product: 9.64 x 23.81 x 14.17
Net weight: 9.000 lbs
Gross weight: 15.000 lbs
Motor location: Integrated motor in hood body
No-return airflow flap: Yes
Length electrical supply cord: 150 cm
Dimensions of the product, with chimney (if exists): .x 534.0 x 300.0 mm
Dimensions of the packed product (HxWxD): 245 x 605 x 360 mm
Net weight: 4.3 kg
Gross weight: 6.8 kg



4 242005 124909

**Series 2, canopy cooker hood, 53 cm,
Stainless steel
DLN53AA50B**

**The canopy cooker hood: offers you
flexibility in your kitchen planning - mount
it either on the wall or above a kitchen
island.**

Variant:

Design:

- Canopy hood

Comfort:

- Suitable for ducted or re-circulated extraction
- For installation in a modified cupboard, above a hob
- Sliding switch control for extractor speeds and light
- 3 speeds
- Paper grease filter with saturation indicator

Environment and safety:

- Energy Efficiency Class: D*
- Average Energy Consumption: 66.7 kWh/year*
- Blower Efficiency Class: E*
- Lighting Efficiency Class: D*
- Grease Filtering Efficiency Class: D*

Technical information:

- Power rating: 121 W
- Noise min./max. Normal Level: 46/61 dB*
- Light Intensity: 78 lux
- Colour Temperature: 2700 K

Measures:

- 120 mm diameter pipe

Optional accessories

- Charcoal odour filter DHZ7304
- grease filter DHZ2100

* In accordance with the EU-Regulation No 65/2014

**Series 2, canopy cooker hood, 53 cm,
Stainless steel
DLN53AA50B**

