

Series 4, gas hob, 60 cm, Tempered glass, Black POP6C6P30M



The gas hob with side-mounted controls: the desired cooking zones can be conveniently operated from the side.

 Four powerful gas burners allows you to cook multiple dishes with a full range BTU performance.

| Product name/family:gas hob w integrated controls |
|--|
| Built-in / Free-standing: |
| Energy input:Gas |
| Total number of positions that can be used at the same time: 4 |
| Required niche size for installation (HxWxD): 45 x 560-562 x 480-490 |
| mm |
| Width of the appliance: |
| Dimensions: |
| Dimensions of the packed product (HxWxD): 145x570x615 mm |
| Net weight: |
| Gross weight: |
| Residual heat indicator: |
| Location of control panel:Lateral |
| Basic surface material: |
| Color of surface: Black |
| Length electrical supply cord: |
| Knob Material:Plastic |
| Sealed Burners: No |
| Power of heating element (kW): |
| Power of 3rd heating element (kW): |
| Power of 5th heating element (kW): |
| Connection rating: |
| Gas connection rating: |
| Fuse protection: |
| Voltage: 220-240 V |
| Frequency: 50; 60 Hz |
| Energy input: |
| Gas type preset:Liquidgas G30,31 28-30/37 mbar |
| Certified gas types:Nat gas H/E/(L) 20 (25) mbar |
| Plug type: |
| |
| Appliance Dimensions (h x w x d) (in): |
| Dimensions of the packed product: 5.70 x 24.21 x 22.44 |
| Net weight:23.000 lbs |
| Gross weight: |
| Total number of positions that can be used at the same time: 4 |
| Length electrical supply cord: |
| Required niche size for installation (HxWxD): 45 x 560-562 x 480-490 |
| mm |
| Dimensions: |
| Dimensions of the packed product (HxWxD): 145x570x615 mm |
| Net weight: 10.6 kg |
| Gross weight: |
| |





Series 4, gas hob, 60 cm, Tempered glass, Black POP6C6P30M

The gas hob with side-mounted controls: the desired cooking zones can be conveniently operated from the side.

- Gas hob with integrated controls, 60 cm

Design

- Steel single pan supports

Usage convenience

- One-hand ignition via control knob: just push and turn the knob to ignite the flame.

Burners and power

- 4 PC
- Left front: Rapid burner up to 3 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: Standard burner up to 1.75 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Safety

- Full flame safety: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)


- Preset of liquid gas (28-30/37mbar)
- Nozzle set for Natural gas nozzles (20 mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): $56 \times 590 \times 520$
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 490)
- Min. worktop thickness: 30 mm
- Power cord 1.5 m with plug: plug and play, no electrician required for installation.
- Connected load: 7.5 KW

Accessories

- cross support for espresso included



Series 4, gas hob, 60 cm, Tempered glass, Black POP6C6P30M



- A: Min. distance from the hob cut-out to the wall
- **B**: Position of gas connection in the cut-out
- C: With fitted oven underneath possibly more; see space requirements for the oven